



TABLE TOP ABSORPTION REFRIGERATORS

Conversion overview



Replace your current table top refrigerator with one of our latest models. Locate your current model and find out which replacement model fits your RV. Please note that this comparison is based on dimensions only. Installation conditions, like vent position, might differ from your current installation. Please always refer to the installation manual, for an optimal replacement.

NOTE refrigeration operation installed models:

P, E: Electric (e.g. N112 1P, N145 6E)
E+, A: Automatic (e.g. N100 6A, N3141-E+, N3170-A)

Table top - 486 x 821 mm (w x h)

INSTALLED MODEL					THETFORD REPLACEMENT				
	Depth	Door	Wheel arch	Technology	Model	Display	Depth	Door	Wheel arch
THETFORD N80 1P / N80 2E / N3080-E	543 mm	Flat	Yes	Absorption	N4080-E+	LED	543 mm	Flat	Yes
Dometic RM 6270 / RM 6271 / RM 6275 / RM 7270 / RM 7271 / RM 7275	541 mm	Flat	Yes	Absorption					

Table top - 525 mm x 821 mm (w x h)

INSTALLED MODEL					THETFORD REPLACEMENT				
	Depth	Door	Wheel arch	Technology	Model	Display	Depth	Door	Wheel arch
THETFORD N90 1P / N90 2E N3090-E / N3090-A	543 mm	Flat	Yes	Absorption	N4090-E+	LED	543 mm	Flat	Yes
Dometic RM 6290 / RM 6291 / RM 7290 / RM 7291 / RM 7295	541 mm	Flat	Yes	Absorption					
RMS 10.5S / RMS 10.5T	548 mm	Flat	Yes	Absorption					

INSTALLED MODEL					THETFORD REPLACEMENT				
	Depth	Door	Wheel arch	Technology	Model	Display	Depth	Door	Wheel arch
THETFORD N97 1P / N97 2E N97 6E / N97 6A N3097-E / N3097-A	578 mm	Curved	Yes	Absorption	No 1:1 replacement available Thetford N4090-E+ can be used when below points are taken into consideration: • N4090-E+ has a flat door				
Dometic RMS 8500 / RMS 8501 / RMS 8505	569 mm	Curved	Yes	Absorption					

Table top - 525 mm x 821 mm (w x h)

INSTALLED MODEL					THETFORD REPLACEMENT				
	Depth	Door	Wheel arch	Technology	Model	Display	Depth	Door	Wheel arch
THETFORD N3108-E / N3108-A	593 mm	Flat	Yes	Absorption	No 1:1 replacement available. Thetford N4090-E+ can be used when below points are taken into consideration: • N4090-E+ is 50mm less deep • N4090-E+ is a LED model • Adaptation of power supply and gas connection could be necessary • A baffle must be created to ensure proper airflow • The use of a ventilator is strongly advised • When present: Frame to position refrigerator against must be moved • New installation must be according the installation instructions				
Dometic RM 7540 L / RM 7541 L / RM 7545 L RMS 10.5XS / RMS 10.5XT	596 mm 603 mm	Flat Flat	Yes Yes	Absorption Absorption					

INSTALLED MODEL					THETFORD REPLACEMENT				
	Depth	Door	Wheel arch	Technology	Model	Display	Depth	Door	Wheel arch
THETFORD N112 1P / N112 2E N112 6E / N112 6A N3112-E / N3112-A	632 mm	Curved	Yes	Absorption	No 1:1 replacement available. Thetford N4090-E+ can be used when below points are taken into consideration: • N4090-E+ is 50mm less deep • N4090-E+ is a LED model • N4090-E+ has a flat door • Adaptation of power supply and gas connection could be necessary • A baffle must be created to ensure proper airflow • The use of a ventilator is strongly advised • When present: Frame to position refrigerator against must be moved • New installation must be according the installation instructions				
Dometic RM 7550 L+ / RM 7551L / RM 7555L+ RMS 8550 / RMS 8551 / RMS 8555	623 mm 624 mm	Curved Curved	Yes Yes	Absorption Absorption					

INSTALLED MODEL					THETFORD REPLACEMENT				
	Depth	Door	Wheel arch	Technology	Model	Display	Depth	Door	Wheel arch
THETFORD N100 1P / N100 2E N100 6E / N100 6A N3100-E / N3100-A N4100-E+ / N4100-A	543 mm	Flat	No	Absorption	No 1:1 replacement available. Thetford N4090-E+ can be used when below points are taken into consideration: • N4090-E+ is a wheel arch model • N4090-E+ is a LED model • Adaptation of power supply and gas connection could be necessary • Vent position is different • The use of a ventilator is strongly advised • When present: Frame to position refrigerator against must be moved • New installation must be according the installation instructions				
Dometic RM 6400 / RM 6401 / RM 6405 / RM 7400 / RM 401 / RM 7405	541 mm	Flat	No	Absorption					

INSTALLED MODEL					THETFORD REPLACEMENT				
	Depth	Door	Wheel arch	Technology	Model	Display	Depth	Door	Wheel arch
THETFORD N104 1P / N104 2E N104 6E / N104 6A N3104-E / N3104-A N4104-E+ / N4104-A	578 mm	Curved	No	Absorption	No 1:1 replacement available. Thetford N4090-E+ can be used when below points are taken into consideration: • N4090-E+ is a wheel arch model • N4090-E+ has a flat door • N4090-E+ is a LED model • Adaptation of power supply and gas connection could be necessary • Vent position is different • The use of a ventilator is strongly advised • When present: Frame to position refrigerator against must be moved • New installation must be according the installation instructions				
Dometic model RM 7400 L+ / RM 7401 L+ / RM 7405 L+	568 mm	Curved	No	Absorption					
Dometic model RM 8500 / RM 8501 / RM 8505	569 mm	Curved	No	Absorption					

LARGE ABSORPTION REFRIGERATORS

Conversion overview



Replace your current large refrigerator with one of our latest models. Locate your current model and find out which replacement model fits your RV. Please note that this comparison is based on dimensions only. Installation conditions, like vent position, might differ from your current installation. Please always refer to the installation manual, for an optimal replacement.

NOTE refrigeration operation installed models:

P, E, E+: Electric (e.g. N112 1P, N145 6E, N3141-E+)
 A: Automatic (e.g. N100 6A, N3170-A)

Large - 418 x 1500 mm (w x h)

INSTALLED MODEL					REPLACEMENT MODEL				
	Depth	Door	Wheel arch	Cooling technology	Model	Display	Depth	Door	Wheel arch
THETFORD N3141-E / N3141-E+ / N3141-A	561 mm	Flat	No	Absorption	N4141-E+ N4141-A	LED LCD Touch	561 mm	Flat	No
THETFORD N3142-E / N3142-E+ / N3142-A	561 mm	Flat	No	Absorption	N4142-E+ N4142-A	LED LCD Touch	561 mm	Flat	No

Large - 525 mm x 1245 mm (w x h)

INSTALLED MODEL					REPLACEMENT MODEL				
	Depth	Door	Wheel arch	Cooling technology	Model	Display	Depth	Door	Wheel arch
THETFORD N145 6E / N145 6A N3145-E / N3145-A	543 mm	Flat	No	Absorption	N4145-E+ N4145-A	LED LCD Touch	543 mm	Flat	No
Dometic model RM 6501 / RM 6505	545 mm	Flat	No	Absorption					
RM 7601 L / RM 7605 L	543 mm	Flat	No	Absorption					
RMD 10.5 / RMD 10.5T	550 mm	Flat	No	Absorption					
THETFORD N150 6E / N150 6A N3150-E / N3150-A	578 mm	Curved	No	Absorption	N4150-E+ N4150-A	LED LCD Touch	578 mm	Curved	No
Dometic model RM 7651 L+ / RM 7655 L+	570 mm	Curved	No	Absorption					
RMD 8501 / RMD 8505	568 mm	Curved	No	Absorption					

Large - 525 mm x 1245 mm (w x h)

INSTALLED MODEL					REPLACEMENT MODEL				
	Depth	Door	Wheel arch	Cooling technology	Model	Display	Depth	Door	Wheel arch
THETFORD N3170-E / N3170-A	593 mm	Flat	No	Absorption	N4170-E+ N4170-A	LED LCD Touch	593 mm	Flat	No
Dometic model RM 7801 L / RM 7805 L	599 mm	Flat	No	Absorption					
RMD 10.5X / RMD 10.5XT	605 mm	Flat	No	Absorption					

INSTALLED MODEL					REPLACEMENT MODEL				
	Depth	Door	Wheel arch	Cooling technology	Model	Operation	Depth	Door	Wheel arch
THETFORD N175 6E / N175 6A N3175-E / N3175-A	628 mm	Curved	No	Absorption	N4175-E+ N4175-A	Electric Automatic	628 mm	Curved	No
Dometic model RM 7851 L+ / RM 7855 L / RML 8551 / RML 8555	626 mm	Curved	No	Absorption					
RMD 8551 / RMD 8555	623 mm	Curved	No	Absorption					

AUSTRALIAN MODELS - Large - 525 mm x 1245 mm (w x h)

INSTALLED MODEL					REPLACEMENT MODEL				
	Depth	Door	Wheel arch	Cooling technology	Model	Operation	Depth	Door	Wheel arch
THETFORD N3185-E+ / N3185-A	628 mm	Curved	No	Absorption	N4175-A AUSTRALIA	Automatic	628 mm	Curved	No
Dometic model RMD 8555 / RMDX 25	622 mm	Curved	No	Absorption					

12V COMPRESSOR REFRIGERATORS

Conversion overview



Replace your current refrigerator with one of our latest 12V compressor models. Locate your current model and find out which replacement model fits your RV. Please note that this comparison is based on dimensions only. Installation conditions, like vent position, might differ from your current installation. Please always refer to the installation manual, for an optimal replacement.

NOTE refrigeration operation installed models:

P, E: Electric (e.g. N112 1P, N145 6E)
E+, A: Automatic (e.g. N100 6A, N3170-A, N3141-E+)

Small - 418 x 975 mm (w x h)

INSTALLED MODEL					REPLACEMENT MODEL				
	Depth	Door	Wheelarch	Cooling technology	Model	Operation	Depth	Door	Wheel arch
THETFORD T1090	486 mm	Flat	No	Compressor	T2090	Capacitive touch	486 mm	Flat	No
Dometic model RC10.4.90(S)(T)	485 mm	Flat	No	Compressor					

Large - 418 x 1500 mm (w x h)

INSTALLED MODEL					REPLACEMENT MODEL				
	Depth	Door	Wheelarch		Model	Operation	Depth	Door	Wheel arch
THETFORD T1152	569 mm	Flat	No	Compressor	T2152	Capacitive touch	569 mm	Flat	No
Thetford model N3141/ N3142/ N4141/ N4142	561 mm	Flat	No	Absorption					

Large - 525 x 1245 mm (w x h)

INSTALLED MODEL					REPLACEMENT MODEL				
	Depth	Door	Wheel arch	Cooling technology	Model	Operation	Depth	Door	Wheel arch
THETFORD N145 / N3145 / N4145	543 mm	Flat	No	Absorption	T2160	Capacitive touch	563 mm	Flat	No
THETFORD N150 / N3150 / N4150	578 mm	Curved	No	Absorption					
Dometic model RM 6501 / RM 6505	545 mm	Flat	No	Absorption					
RM 7601 L / RM 7605 L	543 mm	Flat	No	Absorption					
RMD 10.5T	550 mm	Flat	No	Absorption					
RM 7651 L+ / RM 7655 L+	570 mm	Curved	No	Absorption					
RMD 8501 / RMD 8505	568 mm	Curved	No	Absorption					

INSTALLED MODEL					REPLACEMENT MODEL				
	Depth	Door	Wheelarch	Cooling technology	Model	Operation	Depth	Door	Wheel arch
THETFORD N3170//N4170	593 mm	Flat	No	Absorption	T2175	Capacitive touch	613 mm	Flat	No
THETFORD N175/ N3175/N4175	628 mm	Curved	No	Absorption					
Dometic model RMD 10.5XT	605 mm	Flat	No	Absorption					
RM 7851 L+ / RM 7855 L / RML 8551 / RML 8555	626 mm	Curved	No	Absorption					
RMD 8551 / RMD 8555	623 mm	Curved	No	Absorption					